

The Flat Freddie 30 extrusion is a close cousin of Downhill Dan 30, but with a squarer profile for a more architectural look. It also features a more efficient diffuser for maximum output. Utilizing up to a 2650 lumen per metre LED strip, the profile is ideal for applications where maximum light output is key. A versatile system suitable for various mounting options, Flat Freddie 30 can be surface mounted, wall mounted, suspended and recessed utilising our trimless recess cowlng accessories.

MOUNTING OPTIONS		DIFFUSER OPTIONS		SUPER SERIES LED STRIP OPTIONS			
Surface mounted	Satin	Lumens per metre	Watts per metre	Colour temp.	Lumens per metre	Watts per metre	Colour temp.
Wire suspended	Prismatic	310lm	3W	2700K	1955lm	20W	2700K
Rod suspended		330lm		3000K	2060lm		3000K
Recessed		345lm		4000K	2160lm		4000K
Wall mounted		760lm	7W	2700K	2400lm	26W	2700K
		800lm		3000K	2530lm		3000K
		840lm		4000K	2650lm		4000K
		1520lm		2700K			
		1600lm	14W	3000K			
		1680lm		4000K			

NZ designed and made!


- LED strip options vary depending on region - please consult your local distributor for more information. Other LED strip options are available on request, including IP54 and IP67.
- All lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.
- 5 year manufacturer's warranty on Super Series & Spec Series LED strip.

ACCESSORIES

MC-30 Mounting clip	JN-ST-12 Straight joiner	JN-90-12 90 degree joiner	JN-120-12 120 degree joiner	JN-135-12 135 degree joiner	WB-DD30 Wall bracket	CB-60-R-S / CB-60-R-W / CB-60-R-B Cable base 60, recessed
CB-80-SM-S / CB-80-SM-W / CB-80-SM-B Cable base 80, surface mount	SWK-1-1M / SWK-1-2M / SWK-1-4M Wire suspension	SRK-1-S / SRK-1-W / SRK-1-B Rod suspension kit (rod not incl.)	SRK-6-S / SRK-6-W / SRK-6-B Rod suspension kit (rod not incl.)	ROD-0.5M / ROD-1M / ROD-2M Suspension rod - 0.5m, 1m, 2m	DR-EN-1 (no suspension) DR-EN-1-SWK-1-1M (with 1m wire suspension) DR-EN-1-SWK-1-2M (with 2m wire suspension) DR-EN-1-SWK-1-4M (with 4m wire suspension) Driver enclosure for 100W Triac dimmable driver (with or without integrated wire suspension)	DR-EN-2 (no suspension) DR-EN-2-SWK-1-1M (with 1m wire suspension) DR-EN-2-SWK-1-2M (with 2m wire suspension) DR-EN-2-SWK-1-4M (with 4m wire suspension) Driver enclosure for Tridonic dimmable & non-dimmable driver (with or without 1m, 2m or 4m integrated wire suspension)
C-30-I Recessing cowlng	C-30-EC-I Recessing cowlng end cap	C-30-CNR-2M Corner recessing cowlng	C-30-CNR-EC Corner recessing cowlng end caps (left & right)	C-30-JN Cowlng joiner		

ADDITIONAL INFORMATION

Applications	General downlighting in kitchens, living rooms, dining rooms, reception counters.
Installation	Interior or exterior (with IP65/IP67 rated LED strip).
Materials	Extruded aluminium body, PMMA diffuser, aluminium end caps.
Finish	Natural silver anodised or custom powder coat.
Light source	LED ribbon strip.
Power supply	24V DC - remote driver options ranging from 6W up to 320W.
Dimmable	Various options available, please enquire.



Polar curve for 2250 lumen LED strip with satin diffuser.

