



Richie Rail 17 is a unique illuminated handrail system. CNC machined wall brackets provide a beautiful finish and make for quick installation. Hollow wall brackets conceal the power supply to the LED strip, and the low voltage input makes the handrail safe to touch. Richie Rail 17 is suitable for use on residential and commercial stairs and thoroughfares.

MOUNTING OPTIONS	DIFFUSER OPTIONS	SUPER SERIES LED STRIP OPTIONS		
Wall mounted	Opal	Lumens per metre	Watts per metre	Colour temp.
Glass mounted	Clear	310lm	3W	2700K
		330lm		3000K
		345lm		4000K
		760lm	7W	2700K
		800lm		3000K
		840lm		4000K
		1520lm	14W	2700K
		1600lm		3000K
		1680lm		4000K

- LED strip options vary depending on region - please consult your local distributor for more information. Other LED strip options are available on request, including IP67 and RGBW colour change.
- All lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.
- 5 year manufacturer's warranty on Super Series LED strip.

ACCESSORIES

WBRR17-HS (hollow) WBRR17-SS (solid) Wall bracket with square cover	WBRR17-HR (hollow) WBRR17-SR (solid) Wall bracket with round cover	JN-RR17 Straight joiners	WBPBS-10 Plasterboard spacer, 10mm	WBPBS-13 Plasterboard spacer, 13mm	JN-90-RR17 90 degree bend	JN-V-RR17 Variable angle bend
GMBRR17-SS Glass mount bracket with square cover	GMBRR17-SR Glass mount bracket with round cover	YH24-1502CV Remote emergency pack (for use with Offspring Profiles Spec Series Emergency LED strips only)				

ADDITIONAL INFORMATION

Applications	Residential or commercial stairs, lift cars, accessways.
Installation	Interior or exterior (with IP67 rated LED strip).
Materials	Extruded aluminium body and components, polycarbonate diffuser.
Finish	Powder coated.
Light source	LED ribbon strip.
Power supply	24V DC - remote driver options ranging from 6W up to 320W.
Dimmable	Various options available, please enquire.
Warranty	5 years. Consult full warranty statement for further details.



