



Richie Rail 26 is a unique, 316 stainless steel illuminated handrail system with a diameter of 48.3mm. Hollow wall brackets conceal the power supply to the LED strip, and the low voltage input makes the handrail safe to touch. The innovative sliding wall brackets allow minimal power feeds to the LED strip for simple installation. Richie Rail 26 is suitable for use on residential and commercial stairs and thoroughfares including accessible routes and exterior urban spaces. Richie Rail 26 can be supplied as a “plug-and-play” modular system, or as a seamless, welded system. An optional AS/NZS 2293 compliant emergency system makes Richie Rail 26 a valuable solution for commercial accessways.

| MOUNTING OPTIONS | DIFFUSER OPTIONS | SUPER SERIES LED STRIP OPTIONS | | |
|------------------|------------------|--------------------------------|-----------------|--------------|
| Wall mounted | Opal | Lumens per metre | Watts per metre | Colour temp. |
| Post-top | Clear | 310lm | 3W | 2700K |
| | | 330lm | | 3000K |
| | | 345lm | | 4000K |
| | | 760lm | 7W | 2700K |
| | | 800lm | | 3000K |
| | | 840lm | | 4000K |
| | | 1520lm | 14W | 2700K |
| | | 1600lm | | 3000K |
| | | 1680lm | | 4000K |

- LED strip options vary depending on region - please consult your local distributor for more information. Other LED strip options are available on request, including IP67 and RGBW colour change.
- All lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.
- 5 year manufacturer's warranty on Super Series LED strip.

ACCESSORIES

| | | | | | | |
|--|---|--|--|--|---|--|
| | | | | | | |
| WBRR-SS (satin finish) WBRR-SS-POL (polished finish) Wall bracket | HR-RR26-SS (satin finish) HR-RR26-SS-POL (polished finish) Handrail, 316 stainless steel | EX-RR26-MSA Extrusion | EC-RR26-SS (satin finish) EC-RR26-SS-POL (polished finish) End cap | JN-ST-RR26-SS (satin finish) JN-ST-RR26-SS-POL (polished finish) Straight joiner | JN-90-RR26-SS (satin finish) JN-90-RR26-SS-POL (polished finish) 90 degree joiner | JN-VD-RR26-SS (satin finish) JN-VD-RR26-SS-POL (polished finish) Variable joiner, down |
| | | | | | | |
| JN-VU-RR26-SS (satin finish) JN-VU-RR26-SS-POL (polished finish) Variable joiner, up | JN-TUBE-26-SS (satin finish) JN-TUBE-26-SS-POL (polished finish) Joiner tube, for welded systems only | JN-180-RR26-W-SS (satin finish) JN-180-RR26-W-SS-POL (polished finish) 180 degree joiner tube, for welded systems only | EC-TUBE-26-SS (satin finish) EC-TUBE-26-SS-POL (polished finish) End cap for blank tube, for welded systems only | PTBRR-SS (satin finish) or PTBRR-POL (polished finish) Post top bracket | GMBRR-SS (satin finish) Glass mount bracket | FF-RR26-SS Surface mount flange for JN-TUBE-26-SS, post mount |
| | | | | | | |
| FF-CC-26-SS (satin finish) FF-CC-26-SS-POL (polished finish) Surface mount flange cover cap for FF-RR26-SS | YH24-1502CV Remote emergency pack (for use with Offspring Profiles Spec Series Emergency LED strips only) | SP-RR26-30-IP20 (IP20 version) SP-RR26-30-IP66 (IP66 version) 0.5W 3000K asymmetric LED spot, IP20 or IP66 | | | | |

ADDITIONAL INFORMATION

| | |
|--------------|--|
| Applications | Commercial stairs, public stairs, accessible routes, exterior urban spaces. |
| Installation | Interior or exterior (with IP67 rated LED strip). |
| Materials | 316 stainless steel rail and components, extruded aluminium, polycarbonate diffuser. |
| Finish | Satin 316 stainless steel. |
| Light source | LED ribbon strip. |
| Power supply | 24V DC - remote driver options ranging from 6W up to 320W. |
| Dimmable | Various options available, please enquire. |
| Warranty | 5 years. Consult full warranty statement for further details. |

