

Trimless Tim 15 is designed to recess seamlessly into joinery to offer dot-free lighting solutions. The small ribs either side of the profile allow Trimless Tim 15 to be friction-fitted into an 18mm routed slot in joinery without the need for screws. The flat diffuser provides an excellent, flush, high-level finish to the installation.

MOUNTING OPTIONS

Recessed

DIFFUSER OPTIONS

Opal

Clear

SUPER SERIES LED STRIP OPTIONS

Lumens per metre	Watts per metre	Colour temp.
310lm	3W	2700K
330lm		3000K
345lm		4000K
760lm	7W	2700K
800lm		3000K
840lm		4000K
1520lm	14W	2700K
1600lm		3000K
1680lm		4000K

- LED strip options vary depending on region – please consult your local distributor for more information. Other LED strip options are available on request, including IP54 and IP67.

- All lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.

- 5 year manufacturer's warranty on Super Series & Spec Series LED strip.

ACCESSORIES




JN-ST
Straight joiner



JN-90
90 degree joiner

ADDITIONAL INFORMATION

Applications	Task lighting in kitchen cabinetry, lighting for shelving or display units.
Installation	Interior and exterior (with IP67 rated LED strip).
Materials	Extruded aluminium body, polycarbonate diffuser, AES plastic end caps.
Finish	Natural silver anodised or custom powder coat.
Light source	LED ribbon strip.
Power supply	24V DC - remote driver options ranging from 6W up to 320W.
Dimmable	Various options available, please enquire.



Polar curve for 1340 lumen LED strip with opal diffuser.

